

SAFETY DATA SHEET

JEFFTREAT® M-510

Section 1. Identification

GHS product identifier : JEFFTREAT® M-510
Product code : 00020571
Other means of identification : Not available.
Product type : Liquid.
Material uses : Gas treating
Supplier's details : Huntsman International LLC
P.O. Box 4980
The Woodlands, TX 77387

Technical Information: (281) 719-7780

e-mail address of person responsible for this SDS : MSDS@huntsman.com


Emergency telephone number (24h/7day) : Chemtrec: (800) 424-9300 or (703) 527-3887

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 1B
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : Causes severe skin burns and eye damage.

Precautionary statements : Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Methyldiethanolamine	60 - 100	105-59-9
2-(2-Aminoethoxy)ethanol	13 - 30	929-06-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes severe burns.
- Ingestion** : May cause burns to mouth, throat and stomach.

Section 4. First aid measures

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

- Flash point** : Closed cup: >132°C (>269.6°F)

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
Carbon monoxide
nitrogen oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

- Methods and materials for containment and cleaning up** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Thermal hazards** : Not available.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Yellowish.
- Odor** : Ammoniacal.
- Odor threshold** : Not available.
- pH** : 11.1
- Melting point/Freezing point** : -38°C (-36.4°F)

Section 9. Physical and chemical properties

Boiling/condensation point	: >100°C (>212°F)
Flash point	: Closed cup: >132°C (>269.6°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: >1 [Air = 1]
Relative density	: 1.04
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 0.323 cm ² /s (32.3 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Endpoint	Species	Result
Methyldiethanolamine	-	LC50 Inhalation Dusts and mists	Rat - Male, Female	>6.5 mg/m ³
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit - Male	10244 mg/kg
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit - Female	11336 mg/kg
2-(2-Aminoethoxy)ethanol	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	4680 mg/kg
	OECD 403 Acute Inhalation Toxicity	LC50 Inhalation Vapor	Rat - Male, Female	>8.7 mg/m ³
	OECD 402 Acute Dermal Toxicity	LD50 Dermal	Rabbit - Male, Female	>3000 mg/kg

Section 11. Toxicological information

	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	3400 mg/kg
--	------------------------------	-----------	--------------------	------------

Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Methyldiethanolamine	-	Rabbit	Eyes - Severe irritant
2-(2-Aminoethoxy)ethanol	-	Rabbit	Skin - Moderate irritant
	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Corrosive
	No official guidelines	Rabbit	Eyes - Corrosive

Conclusion/Summary

- Skin** : Methyldiethanolamine Irritating to skin.
2-(2-Aminoethoxy)ethanol Corrosive to the skin.
- Eyes** : Methyldiethanolamine Severely irritating to eyes.
2-(2-Aminoethoxy)ethanol Corrosive to eyes.
- Respiratory** : Methyldiethanolamine No additional information.
2-(2-Aminoethoxy)ethanol No additional information.

Sensitization

Product/ingredient name	Test	Route of exposure	Species	Result
Methyldiethanolamine	-	skin	Guinea pig	Not sensitizing
2-(2-Aminoethoxy)ethanol	OECD 406 Skin Sensitization	skin	Guinea pig	Not sensitizing

Mutagenicity

Product/ingredient name	Test	Result
Methyldiethanolamine	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vitro Subject: Mammalian-Animal Metabolic activation: +/-	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative
2-(2-Aminoethoxy)ethanol	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic	Negative
	Experiment: In vitro Subject: Mammalian-Animal	Negative
	Experiment: In vivo Subject: Mammalian-Animal	Negative

- Conclusion/Summary** : 2-(2-Aminoethoxy)ethanol No mutagenic effect.

Carcinogenicity

Section 11. Toxicological information

Conclusion/Summary :

2-(2-Aminoethoxy)ethanol In accordance with column 2 of Annex VII - X of Regulation (EC) No 1907/2006, the test for this property of the substance does not need to be conducted.

Reproductive toxicity

Product/ingredient name	Test	Species	Maternal toxicity	Fertility	Developmental effects
2-(2-Aminoethoxy)ethanol	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Rat - Male, Female	Negative	Negative	Negative
	OECD 411 Subchronic Dermal Toxicity: 90-day Study	Rat - Male, Female	Negative	-	-

Teratogenicity

Product/ingredient name	Test	Species	Result/Result type
Methyldiethanolamine 2-(2-Aminoethoxy)ethanol	- OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Rat - Male, Female Rat - Male, Female	Negative - Dermal Negative - Inhalation

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes severe burns.

Section 11. Toxicological information

Ingestion : May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur

Ingestion : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Test	Endpoint	Species	Result
Methyldiethanolamine	EPA CFR	Sub-chronic NOAEL Dermal	Rat - Male, Female	750 mg/kg
2-(2-Aminoethoxy)ethanol	OECD 411 Subchronic Dermal Toxicity: 90-day Study	Sub-chronic NOAEL Dermal	Rat - Male, Female	>175 mg/kg/d
	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Sub-chronic NOEC Inhalation Vapor	Rat - Male, Female	4 mg/m ³

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Section 11. Toxicological information

Route	ATE value
Oral	4465.9 mg/kg

Other information : Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
Methyldiethanolamine	DIN DIN 38412 Part 8	Acute EC50	17 hours	Bacteria	413.8 mg/l
	EU	Acute EC50	48 hours Static	Daphnia	233 mg/l
	DIN DIN 38412 part 9	Acute ErC50 (growth rate)	72 hours	Algae	176 mg/l
2-(2-Aminoethoxy)ethanol	DIN DIN 38412 Part 15	Acute LC50	96 hours Static	Fish	1000 to 2200 mg/l
	DIN DIN 38412 Part 8	Acute EC50	17 hours Static	Bacteria	110 mg/l
	EU EC C.2 Acute Toxicity for Daphnia	Acute EC50	48 hours Static	Daphnia	189 mg/l
	DIN DIN 38412 part 9	Acute ErC50 (growth rate)	72 hours Static	Algae	202 mg/l
	DIN DIN 38412 Part 15	Acute LC50	96 hours Static	Fish	>681 mg/l
	DIN DIN 38412 Part 8	Chronic EC10	17 hours Static	Bacteria	28 mg/l
	DIN DIN 38412 part 9	Chronic NOECr	72 hours Static	Algae	62.5 mg/l

Persistence and degradability

Product/ingredient name	Test	Period	Result
Methyldiethanolamine	OECD 301A Ready Biodegradability - DOC Die-Away Test	18 days	96 %
2-(2-Aminoethoxy)ethanol	OECD 301A Ready Biodegradability - DOC Die-Away Test	17 days	90 to 100 %
	OECD 302B Inherent Biodegradability: Zahn-Wellens/EMPA Test	28 days	84 %

Conclusion/Summary : 2-(2-Aminoethoxy)ethanol Readily biodegradable

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Methyldiethanolamine	-	-	Readily
2-(2-Aminoethoxy)ethanol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Methyldiethanolamine	-1.08	3.16	low
2-(2-Aminoethoxy)ethanol	-1.89	-	low

Section 12. Ecological information

Mobility in soil

Not available.

Other adverse effects : No known significant effects or critical hazards.

Other ecological information

BOD5 : Not determined.

COD : Not determined.

TOC : Not determined.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport information



Proper shipping name

DOT : Corrosive liquid, basic, organic, n.o.s. (Alkanolamine)



TDG : Corrosive liquid, basic, organic, n.o.s. (Alkanolamine)

IMDG : Corrosive liquid, basic, organic, n.o.s. (Alkanolamine)

IATA : Corrosive liquid, basic, organic, n.o.s. (Alkanolamine)

Regulatory information	UN number	Classes	PG*	Label	Additional information
DOT Classification	UN3267	8	II		-
TDG Classification	UN3267	8	II		-

Section 14. Transport information

IMDG Classification	UN3267	8	II		Emergency schedules (EmS) F-A S-B
IATA Classification	UN3267	8	II		Passenger and Cargo Aircraft Quantity limitation: 1 L Packaging instructions: 851 Cargo Aircraft Only Quantity limitation: 30 L Packaging instructions: 855

PG* : Packing group

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

United States Regulations

- TSCA 8(b) inventory** : All components are listed or exempted.
- TSCA 5(a)2 final significant new use rule (SNUR)** : No ingredients listed.
- TSCA 5(e) substance consent order** : No ingredients listed.
- TSCA 12(b) export notification** : No ingredients listed.
- SARA 311/312** : Immediate (acute) health hazard
- Clean Air Act - Ozone Depleting Substances (ODS)** : This product does not contain nor is it manufactured with ozone depleting substances.
- SARA 313** : No ingredients listed.

	<u>Ingredient name</u>	<u>%</u>	<u>Section 304 CERCLA Hazardous Substance</u>	<u>CERCLA Reportable Quantity (Lbs)</u>	<u>Product Reportable Quantity (Lbs)</u>
CERCLA Hazardous substances	Ethylene glycol	0.0426	Listed	5000	11737089
	Ethylene oxide	0.00000027	Listed		
	Propylene oxide	0.00000027	Listed	100	37037037037

State regulations

Section 15. Regulatory information

PENNSYLVANIA - RTK : No ingredients listed.

California Prop 65 : **WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>
Ethylene oxide	Yes.	Yes.
Propylene oxide	Yes.	No.

Canadian regulations

CEPA DSL : All components are listed or exempted.

WHMIS Classes : Class D-2B: Material causing other toxic effects (Toxic).
Class E: Corrosive material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Brazil Regulations

Classification system used : Norma ABNT-NBR 14725-2:2012

International lists

Australia inventory (AICS): All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Japan inventory: All components are listed or exempted.
Korea inventory: All components are listed or exempted.
Malaysia Inventory (EHS Register): Not determined.
New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.
Taiwan inventory (CSNN): Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.) :


Health	3
Flammability	1
Physical hazards	0
Personal protection	

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

National Fire Protection Association (U.S.A.) :

Section 16. Other information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing	: 6/30/2014.
Date of issue	: 6/30/2014.
Date of previous issue	: 6/6/2014.
Version	: 2

▣ Indicates information that has changed from previously issued version.

JEFFTREAT® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more countries, but not all countries.

Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.