



SPX INHIBITED TEG

HIGH PERFORMANCE TRIETHYLENE GLYCOL BASED FLUID FOR USE IN NATURAL GAS DEHYDRATION SYSTEMS

SPX Inhibited TEG is a premium performing triethylene glycol based fluid engineered with a superior inhibitor additive package. SPX Inhibited TEG is designed to prevent corrosion and sludge causing improved system efficiency and extended fluid and equipment life.

Features & Benefits

- Protects against corrosion of system components
- Provides superior deposit and oxidation control
- Enhanced sludge control results in improved system cleanliness
- Compatible with materials commonly used in dehydration systems

Applications

- Gas pipeline heaters
- Gas processing
- Air dehydration
- Natural gas storage
- Gas field gathering
- Line and bath heaters
- Waste heat recovery

TYPICAL PROPERTIES

Color	Clear Undyed
Specific Gravity @ 60°F	96.1
Triethylene Glycol wt%	1.9
Inhibitors wt%	1.131
pH of 50% Solution	9.8
Reserve Alkalinity ml	7 min
Boiling Point, °F (°C)	545 (285)
Flash Point, °F (°C)	340 (171)
Freeze Point, °F (°C)	19 (-7)

Minor variations in typical properties data are to be expected in normal manufacturing.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).

