



# SPX SYNTHETIC GL-5 GEAR OIL

SYNTHETIC MULTIPURPOSE EXTREME PRESSURE API GL-5 GEAR LUBRICANT

---

SPX Synthetic GL-5 Gear Oil is a synthetic, API GL-5 automotive gear lubricant. It is specially designed for use in hypoid gear set applications operating in extreme temperatures or under severe conditions. SPX Synthetic GL-5 Gear Oil is formulated to provide long service life and extended gear life in gear applications operating under varying conditions of speed, load, temperature, and torque. The full-synthetic formulation provides enhanced oxidation resistance and thermal stability at high temperatures and better low-temperature properties compared with conventional mineral oil-based gear oils, resulting in longer service intervals and better performance over a wide temperature range.

---

## Features & Benefits

- Extended drain, all-season performance
  - Outstanding oxidation resistance and thermal stability to minimize sludge and varnish formation
  - Excellent thermal durability and extreme-pressure properties for extended gear life
  - High load carrying capacity for protection against scuffing and wear
  - High shear stability
  - Protects against rust and corrosion
  - Compatible with synthetic and conventional automotive gear oils
- 

## Applications

- Service fill of conventional differentials on passenger cars and trucks
  - Service fill of differentials, final drives, and transfer cases in some off-highway equipment
  - Non-synchronized manual transmissions in trucks, buses, and heavy equipment where the manufacturer specifies and API GL-5 or MT-1 gear oil
  - Top drive or mudpump gearboxes on drilling equipment in severe environments
- 

## Specifications

SPX Synthetic GL-5 Gear Oil meets the requirements of the following industry specifications:

- API Service GL-5, MT-1
  - MIL-PRF-2105E
  - SAE J2360
- 

Web: [www.pilotthomas.com](http://www.pilotthomas.com)

Email: [ptl.orders@pilotthomas.com](mailto:ptl.orders@pilotthomas.com)

Tel: 844.785.8326



# SPX SYNTHETIC GL-5 GEAR OIL

## TYPICAL PROPERTIES

SAE Grade	75W-90	80W-140
Specific Gravity @ 60°F	0.874	0.862
Density, lbs/gal @ 60°F	7.26	7.34
Flash Point (COC), °C (°F)	200(392)	200(392)
Pour Point, °C (°F)	-45(-49)	-36(-33)
Viscosity, Brookfield		
cP @ -40°C	119,000	---
cP @ -26°C	---	48,000
Viscosity, Kinematic		
cSt @ 40°C	114	222
cSt @ 100°C	17.2	25.5
Viscosity Index	166	146

Minor variations in typical properties data are to be expected in normal manufacturing.

### Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet (SDS).